

1	直接仮設											
	墨出し(内部改修)			仮設拾い刈							71.3	m2
					71.31				=71.31			
	養生(内部改修)	床養生シート+5mm合板		仮設拾い刈							71.3	m2
					71.31				=71.31			
	整理清掃後片付け(内部改修)			仮設拾い刈							71.3	m2
					71.31				=71.31			
	内部仕上足場	階高4.0未満 架台足場		仮設拾い刈							71.3	m2
					71.31				=71.31			
	内部枠組棚足場	H=5793		仮設拾い刈							194.0	m2
					193.99				=193.99			
	内部枠組棚足場	H=5168		仮設拾い刈							27.0	m2
					27.01				=27.01			
	内部枠組棚足場	H=4450		仮設拾い刈							31.5	m2
					31.50				=31.50			
	外部枠組本足場 (手すり先行足場)	建枠900 仮置きスージ		仮設拾い刈							214.1	m2
					214.11				=214.11			
	内部枠組本足場	建枠900		仮設拾い刈							84.0	m2
					84.03				=84.03			

2

2	内装改修	<改修>										
	<天井>											
	天井 ロックウール吸音板張り	厚9	不燃	内部拾い<天井>引							67.7	m2
		下地PB厚9.5(不燃)共		a	67.70				=67.70			
	天井 石膏ボード張り	厚9.5	準不燃	内部拾い<天井>引							0.6	m2
				h	0.60				=0.60			
	天井 高密度グラスボード張り	厚25		内部拾い<天井>引							0.6	m2
				h	0.60				=0.60			
	軽量鉄骨天井下地	19形	ふところ1.5m未満	内部拾い<天井>引							0.6	m2
		下地張りなし		h	0.60				=0.60			
	軽量鉄骨天井下地	19形	ふところ1.5m未満	内部拾い<天井>引							67.7	m2
		下地張りあり		a	67.70				=67.70			
	軽量鉄骨天井 開口部補強	19形	450x450	内部拾い<天井>引							16.0	か所
					16.00				=16.00			
	軽量鉄骨天井 開口部補強	19形	300φ	内部拾い<天井>引							2.0	か所
					2.00				=2.00			
	天井点検口	7mm製枠	450角	<2F>談話コーナー	3.00				=3.00		3.0	か所

[illegible]